#### AVK-70Z-101&301

#### 150M / 300M CAT5 VGA Extender Kit


The Extender Kit consists of a transmitter and a receiver. It is a VGA Only Extension unit that allows VGA signals be sent up to  $150 \sim 300 \text{M}$  ( $500 \sim 1000 \text{ ft.}$ ) via economical, easy-to-install unshielded twisted pair (UTP) CAT5 cable. It's simple, straight forward plug-and-play. Crisp video imaging and high fidelity sound. Applications: shopping malls, public address systems, educational facilities, transportation stations, boardrooms, stores, restaurants, showrooms, windows displays, trade shows, exhibitions, computer based training.

#### **Features**


- Supports up to 1920 x 1200 @60Hz resolution.
- Receivers have Gain and EQ adjustments for optimum image quality.
- AVK-70Z-301 kit has adds RGB skew adjustment function.
- Supports the latest TFT, LCD, SVGA, VGA multisync monitors and DDC2B high resolution.
- Run a single UTP cable to 300M (1000 feet) from Transmitter (for AVK-70Z-301 kit).
- Razor sharp video.
- Pure hardware, Plug n Play design.

#### Front and Back View


### **AV-702Z-101 Transmitter**



## AV-701Z-101 Receiver




### **AV-701Z-301** Receiver



# **Specification**

Model No.			AV-702Z-101	AV-701Z-101	AV-701Z-301
			Transmitter	Receiver	Receiver
System Cable			CAT5, FTP Solid Wire 2x4x24 AWG,		
			standard 568B RJ-45 connector		
Connectors	System OUT		1 x RJ-45 F	N/A	N/A
	System IN		N/A	1 x RJ-45 F	1 x RJ-45 F
	VGA IN		1 x HDD15 F	N/A	N/A
	VGA OUT		1 x HDD15 F	1 x HDD15 F	1 x HDD15 F
	Video Gain		N/A	1 x Mini Pot	1 x Mini Pot
)uuc	Video EQ		N/A	1 x Mini Pot	1 x Mini Pot
S	Video RGB Skew		N/A	N/A	2 x mini Push button
	Power		1 x Power Jack	1 x Power Jack	1 x Power Jack
	Power LED		1 (Green)	1 (Green)	1 (Green)
	RGB LED		N/A	N/A	3 x R/G/B
Resolution			1920 x 1200@ 60Hz , DDC2B		
Distance		Depends on			
		tanco	receiver, and	0 ~ 150M (500 ft.)	0 ~ 300M (1000 ft.)
		tance	CAT5 cable		
		quality.			
Power Consumption			External 100~240VAC to output DC +5.0V; 1.2A		
		Operating	0 ~ 70°C		
Enviror	ment	Temp.			
Environment		Storage Temp.	-20 ~ 70°C		
		Humidity	0 ~ 80% RH		
	Housing		Metal (Black)		
Phys	ical	Dimensions	12.8 x 11 x 2.9 cm		
Properties		(L x W x H)	12.0 X 11 X 2.5 CIII		
		Weight	375 g	343 g	370 g

### Diagram



## **Ordering Information**

AV-702Z-101 Transmitter	1-port CAT5 VGA Transmitter with local VGA loop-out. (1 VGA In, 1 VGA Out, 1 RJ45 Out)
AV-701Z-101 Receiver	150 meters CAT5 VGA Receiver. (1 RJ45 In, 1 VGA Out), built-in video Gain/Equalizer
AV-701Z-301 Receiver	300 meters CAT5 VGA Receiver. (1 RJ45 In, 1 VGA Out), built-in video Gain/Equalizer and RGB Skew